

-EM2W KOPA EMERGENCY LIGHT

EMERGENCY LIGHT

General

FR100, FS100 or FR140 trim
 FR100/FS100 C0/C90 C80 classification
 3 hour duration
 80 degree diffused optics
 Integrated 2W emergency light
 NiMH environmentally friendly battery
 Rated life 50,000 hours

Driver Details

Standard driver: trailing edge dimmable (K18W-350D)
 Drivers for 12-24V DC supply available on request

Material & Construction

All aluminium with unique copper core heatsink technology
 Silicon seal
 10 year paint treatment (white only)



Machined from
 6063 Aluminium

Options

Dimmable driver 1-10V, DALI, DSI, PUSH DIM, DMX 512 systems
 Non dimmable driver
 Adaptor plug for integration to OEM emergency
 pack from other manufacturers*

Specifications

MODEL	-EM2W - 2W Emergency			
TRIM	FR100-Fixed Round	FS100-Fixed Round	FR140-Fixed Round	
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	7W - 180mA	10W - 260mA	13W - 350mA	18W - 500mA
COLOUR	WH- White	SL- Silver	BL- Black	

MODEL	TRIM	COLOUR TEMP	WATTAGE	COLOUR
-------	------	-------------	---------	--------

Spacing Tables for FR100/FS100 Trim

Mounting Height (m)	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
Maximum Spacing (m)	12.7	13.5	14.4	15.1	15.8	16.5	17.3	18.3	19.1	20.7	22	23	23.9	24.7	26.1	24

AS2293.1-2005 Table 5.3 extract, Luminaire classification (C0/C90) C80



*Speak to your local agent regarding suitable combinations